




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 17/04	A1	(11) International Publication Number: WO 95/24864 (43) International Publication Date: 21 September 1995 (21.09.95)
(21) International Application Number: PCT/US95/03140 (22) International Filing Date: 14 March 1995 (14.03.95) (30) Priority Data: 08/209,278 14 March 1994 (14.03.94) US (71) Applicant: ADVANCED SURGICAL, INC. [US/US]; 305 College Road East, Princeton, NJ 08540 (US). (72) Inventors: HEAVEN, Malcom, D.; 10 Coventry Lane, Hopewell, NJ 08525 (US). CUSCHIERI, Alfred; 6 Balna Carron Avenue, St. Andrews, Fife KY16 9LT (GB). (74) Agent: PETERSON, James, W.; Burns, Doane, Swecker & Mathis, P.O. Box 1404, Alexandria, VA 22313-1404 (US).	(81) Designated States: AU, CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>	

(54) Title: EXTRACORPOREAL PNEUMOPERITONEUM ACCESS BUBBLE

(57) Abstract

A medical device (1) for forming an external extension of the pneumoperitoneum, thus allowing the surgeon more flexibility in a surgical procedure. The device includes an enclosure (2) and an elastically deformable flange or ring (9) at an open end of the enclosure (2). The flange/ring (9) is deformed and inserted into a trocar puncture site, upon which it deploys against the inner surface of the abdominal wall. By maintaining a gentle lifting force on the external portion of the device the neck of the device forms a seal between the opening in the abdominal wall and the "balloon", allowing the insufflation gas to inflate the external balloon. The device includes one or more valved openings (11) which allow access to the interior of the balloon. These openings (11) may be small, allowing access of laparoscopic instruments through the valve, or somewhat larger, allowing the access of a hand or hands.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

EXTRACORPOREAL PNEUMOPERITONEUM ACCESS BUBBLE

FIELD OF THE INVENTION

The present invention relates to improvements in laparoscopic procedures enabled by the use of a device which effectively extends the
5 pneumoperitoneum extracorporeally. The device allows the use of a broader range of instruments, including conventional surgical instruments, and even the direct interaction of the surgeons hands without loss of insufflating gas.

BACKGROUND OF THE INVENTION

Laparoscopic surgery (laparoscopy) is becoming a preferred method for
10 performing various types of surgical operations. However, unlike other types of surgical procedures, laparoscopic surgery does not require large incisions to expose the internal organs. Instead, an insufflation needle, typically a Veress needle, is inserted into the abdominal cavity, and an insufflation gas such as CO₂ used to inflate the cavity. Once safely inflated a trocar is inserted through
15 the original puncture site. On removal of the trocar knife a laparoscope may be inserted through the cannula left insitu, allowing visualization of the interior of the abdomen and safe insertion under direct visualization of further trocars/cannulas as needed. Access for surgical instruments is now available through these extra cannulas. In order to prevent escape of pressurized gas
20 from the body cavity, instrument supporting devices have been proposed in U.S. Patent Nos. 5,137,520; 5,176,648; 5,211,370 and 5,215,531.

Several problems are associated with the sheath, cannula or other similar devices. Such problems include limited access to the organ or organs being worked on, limits on the number of instruments and variety of instruments
25 which can be used during a given procedure, lack of access of the surgeon's hand or hands to the body cavity, limited visibility, lack of protection of the incisions from diseased tissues, organs or cells during removal of the diseased

-2-

tissues, organs or cells and lack of protection of the incision from excessive expansion. Accordingly, there is a need in the art for solutions to the above problems.

SUMMARY OF THE INVENTION

5 The invention provides a medical device forming an extracorporeal pneumoperitoneum access bubble useful in laparoscopic surgical operations. The device includes an enclosure and deploying means at an open end thereof. The deploying means is deformable to a configuration which permits the open
10 end of the enclosure to pass through a trocar puncture site in an abdominal wall. The deploying means also expands the open end of the enclosure beneath an inner surface of the abdominal wall. The enclosure also includes at least one access opening therein for accessing an interior of the enclosure and
15 performing surgical operations beneath the abdominal wall or within the interior of the enclosure.

15 According to various features of the invention, the enclosure can be bulbous in shape and the deploying means can comprise an elastically deformable flange. Alternatively, the deploying means can comprise an elastically deformable ring surrounding the open end of the enclosure. In the
20 case of a ring, the deploying means can comprise a coil spring. The ring can be of a springy material such as an engineering polymer, stainless steel, nickel titanium superelastic alloy, elastomer or other elastic material. In the case
25 where the deploying means comprises a flange which is integral with the enclosure, the enclosure and/or the flange can be of a polyolefin, polyethylene, terephthalate, polybutylene terephthalate, polyvinyl chloride, ionomer,
polyurethane, nylon, polycarbonate, acrylic, ethylene vinyl acetate copolymer, polyvinylidene fluoride or blends thereof.

-3-

The access opening can comprise an iris valve of the fixed or adjustable type. In the case of the adjustable iris valve, the valve can include a rotatable ring which adjusts an opening through the valve. Other valve configurations known to those skilled in the art may also be used. According to a preferred embodiment of the invention, a plurality of valves are provided in the enclosure whereby a variety of tools or instruments can simultaneously be manipulated by the surgeon within a single trocar puncture site.

The enclosure can include a handle at an upper end thereof whereby the deploying means can be pulled into sealing engagement with an inner surface of the abdominal cavity. To allow viewing of the surgical operation, the enclosure can be partly or entirely of a transparent material. A constriction can be provided between the enclosure and the deploying means and the enclosure can either be gas-tight and expandable from a first configuration to a second configuration by supplying pressurized gas to the interior of the enclosure or the enclosure can be rigid and self-supporting. The constriction can be elastically deformable whereby the trocar puncture site can be stretched to a larger size by expansion of the constriction. For instance, the enclosure can be spherical in shape at the open end thereof adjacent the constriction and the constriction can form a narrow passage through which surgical instruments can be inserted into a patient's abdominal cavity.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 shows a medical device in accordance with the invention;

Figures 2a-d show how the medical device of Figure 1 can be deployed in an abdominal wall of a patient;

Figures 3a-d show details of a fixed-type iris valve which can be incorporated in the medical device according to the invention;

-4-

Figures 4a-b show details of an adjustable iris valve which can be incorporated in the medical device according to the invention; and

Figure 5 shows a medical device in accordance with a further embodiment of the invention.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The medical device according to the present invention provides an extension of the pneumoperitoneum during laparoscopic procedures which allows improved access to the organ or organs being worked upon. The device also allows the simultaneous, multiple entry and withdrawal of a wide range of surgical instruments through a single incision in the abdominal wall, and may
10 hence reduce the overall number of puncture sites needed for the procedure. The device can include means for allowing access of the surgeon's hand or hands to the pneumoperitoneum and the device can be of a transparent material which allows clear observation during the surgical procedure. The device aids
15 in reducing the possible spread of disease, for example cancer cells, by preventing contact with the exposed tissue layers at the puncture site, thus allowing safe tissue specimen removal. Moreover, the device atraumatically expands the diameter of the puncture site by gently opening and taking advantage of the elasticity of the tissue. In addition, the device can be
20 manufactured cheaply, with a view to being disposable.

The present invention will allow surgeons to bring the benefits of laparoscopic assisted bowel surgery to their patient by making the procedure easier and more cost efficient. The benefits include (1) a smaller incision, which contributes to significant benefits to the patient, such as less pain, shorter
25 hospital stay, etc., (2) less morbidity by protecting the wound edges from contamination, (3) better resection and anastomosis by allowing the use of standard instruments, and palpation, and (4) an easier learning curve and more

-5-

cost effectiveness, resulting from the ability to use standard instruments and the surgeon's hand.

The present invention provides a medical device which includes an enclosure and deploying means which can be inserted into a trocar puncture site. The deploying means then expands beneath the inner surface of the abdominal wall. By applying a gentle lifting force on the enclosure, the deploying means forms a seal with the abdominal wall allowing insufflation gas in the abdominal cavity to inflate the enclosure into a "balloon" shape. Once inflated, the internal gas pressure in the abdominal cavity maintains the device in a stable shape. The device includes one or more access openings which allow access to the interior of the enclosure, and hence the abdominal cavity. These openings may be small and incorporated in valve mechanisms, allowing access of laparoscopic instruments through such valves. However, in addition to or in lieu of the smaller openings, one or more somewhat larger openings can be provided in the enclosure, allowing access of a hand or hands of a surgeon. Preferably, the valve design is such that loss of pneumoperitoneum is minimized.

Figure 1 shows the overall construction of a device according to a preferred embodiment of the invention. The device includes a transparent enclosure 2 which forms a pneumoperitoneum extension having an open end 3 and an integral deploying means 4 at the open end 3. At least one access opening 5 is provided in the enclosure 2 for sealingly receiving a tool 6.

The enclosure 2 can be of one piece construction or sections made from different materials. For example, the enclosure 2 may consist of very thin, transparent polyolefin material, which may incorporate a slightly thicker neck section 7 to aid positioning of the device 1 in the trocar puncture site. The enclosure 2 may have a spherical shape resembling a globe or any other shape defining an empty space in the interior of the enclosure 2.

-6-

In one embodiment of the present invention, the deploying means 4 is integral with the enclosure 2 and comprises a flat annular flange 9 of springy material which aids in deploying and sealing of the device 1 on the inside of the abdominal wall. The enclosure 2 and deploying means 4 may be integrally
5 molded from the same material, or a separate flexible flange may be incorporated into an open end of the enclosure via welding, bonding, or by any other suitable method known to those skilled in the art. For instance, the enclosure and/or deploying means may be formed via blow-molding, radio frequency welding, dipping, casting, bonding, or any other suitable method
10 known to those skilled in the art.

Suitable materials for the enclosure and flange include, but are not limited to, polyolefins, polyethylene terephthalate, polybutylene terephthalate, polyvinyl chloride, ionomers, polyurethanes, nylons, polycarbonate, acrylics, ethylene vinyl acetate copolymers, polyvinylidene fluoride, and blends and
15 copolymers thereof.

The deploying means 4 may also comprise a separate component such as a ring 10 made from a springy material such as an engineering polymer, stainless steel, a NiTi superelastic alloy, or any other suitably springy material. For instance, the ring 10 can comprise a coil spring shaped into a ring.

20 The deploying means preferably returns to its original shape after being elastically deformed by an external force. For instance, one embodiment of the present invention makes use of the elastic flange 9 or ring 10 that can be deformed (Figures 2a-b) by squeezing the flange/ring to ease insertion of the flange/ring into the incision. Upon insertion and release, the flange/ring will
25 return to its original shape, as depicted in Figures 2c-d.

-7-

In a preferred embodiment, the access opening comprises one or more iris valves 11 constructed from a pair of rings 12 fixed or rotatable with respect to each other and connected to opposite ends of a tube 13 of an elastic material. As shown in Figures 3 a-d, the tube 13 can be supported at each end thereof by rings 12 and by twisting the rings 12 in opposite directions (Figure 3b), an iris valve is formed (Figures 3c-d). Suitable tube materials include, for example, natural rubber, latex or polyurethane elastomers.

The iris valve 11 may be a fixed iris valve 14 wherein the valve is always biased closed due to the resilient tube 13 which is held in a twisted condition, as shown in Figures 1 and 5. The iris valve 11 may also be an adjustable valve 15 wherein one ring is rotatable with respect to the other ring, as shown in Figures 1 and 5. The fixed iris construction allows access of relatively small surgical instruments or tools, e.g., 5 to 20 mm diameter, due to the elasticity of the tube material which allows the body of the instrument to be inserted through the center of the iris. A substantially gas-tight seal is maintained at all times such that the valve sealedly receives the tool or if the valve is large enough a surgeon's hand can be passed therethrough.

For larger objects, such as a hand, it may be desirable to use the adjustable iris valve 15. In this instance, the valve 15 can be quickly opened wide enough to allow passage of a hand and then closed around the wrist of the surgeon to prevent loss of pneumoperitoneum. For instance, the valve 15 can include an inner ring 16 which rotates relative to a fixed outer ring 17, the rings being separated by one or more gears 18, as shown in Figures 4a-b.

Other valve constructions which can be used for the access opening 5 include a re-enterable valve constructed from self-sealing gels. Such gels allow the penetration of objects, yet on withdrawing the invading device they seal behind it as it is withdrawn. Suitable materials include, for example, gels based on lightly cross-linked silicone, vegetable, or fish oils, or blends thereof.

-8-

A valve somewhat like a multi-leaved flapper valve may also be used. Further, for relatively small diameter instruments, it is possible to use an elastomeric insert which contains a pinhole. This allows access to the interior of the enclosure but such a pinhole type valve could be limited with respect to the size of objects which can pass therethrough yet maintain peritoneum after the objects are removed from the pinhole. Other valving systems such as duck bill valves, etc., may also be used.

It is also possible that a glove-like section may be welded or otherwise attached to the enclosure, rather like a conventional glove box. This would allow the surgeon some access to handle organs or instruments without actually using a valve to access the interior of the enclosure. Additional access for large implements can also be obtained by incorporating a gas tight 'zip fastener' section (such as, for example, commonly found on freezer storage bags). Other possible access valve/port systems are known or would be apparent to those skilled in the art.

The device may further incorporate other features which assist or enhance its performance. For example, a handle 19 can be located on the top of the device, to which the surgeon may apply a lifting force during inflation. Such pulling will bring the deploying means into contact against the inner abdominal wall, thus ensuring a very good seal, and rapid inflation of the "bubble" enclosure by the insufflating gas.

In operation, depending on ambient conditions, it may be further advantageous to coat the inner surface of the "bubble" enclosure with a coating such as a hydrophilic coating. Such coatings could be used to prevent fogging of the device due to condensation of moisture from the abdominal cavity, thus preserving a clear field of view.

-9-

According to a further embodiment of the present invention, the enclosure may be rigid, and may or may not require an insufflating gas to deploy it. If a gas is used, the neck section and/or deploying means of the device could be flexible as previously described. For gasless laparoscopic procedures, the neck section of the device could incorporate a retraction section for distension of the trocar puncture site opening.

The foregoing has described the principles, preferred embodiments and modes of operation of the present invention. However, the invention should not be construed as being limited to the particular embodiments discussed. Thus, the above-described embodiments should be regarded as illustrative rather than restrictive, and it should be appreciated that variations may be made in those embodiments by workers skilled in the art without departing from the scope of the present invention as defined by the following claims.

-10-

WHAT IS CLAIMED IS:

1. A medical device for forming an extracorporeal pneumoperitoneum extension comprising an enclosure and deploying means at an open end of the enclosure, the deploying means being deformable to a configuration which
5 permits the open end to pass through a trocar puncture site in an abdominal wall and then expand the open end beneath an inner surface of the abdominal wall, the enclosure including at least one access opening therein for accessing an interior of the enclosure and allowing surgical operations to be performed beneath the abdominal wall or within the interior of the enclosure.
- 10 2. The device of claim 1, wherein the enclosure is bulbous in shape and the deploying means comprises an elastically deformable flange.
3. The device of claim 1, wherein the deploying means comprises an elastically deformable ring surrounding the open end of the enclosure.
- 15 4. The device of claim 1, wherein the deploying means comprises a coil spring.
5. The device of claim 1, wherein the enclosure is of a flexible material selected from the group consisting of a polyolefin, polyethylene terephthalate, polybutylene terephthalate, polyvinyl chloride, ionomer, polyurethane, nylon, polycarbonate, acrylic, ethylene vinyl acetate copolymer, polyvinylidene
20 fluoride or blends thereof.
6. The device of claim 1, wherein the access opening comprises an iris valve.
7. The device of claim 6, wherein the valve is an iris valve having a rotatable ring which adjusts an opening through the valve.

-11-

8. The device of claim 1, wherein the enclosure includes a plurality of access openings at spaced-apart locations on the enclosure.

5 9. The device of claim 1, further comprising a handle attached to the enclosure.

10. The device of claim 1, wherein the enclosure is transparent.

11. The device of claim 3, further comprising a constriction between the enclosure and the deploying means.

12. The device of claim 1, wherein the enclosure is gas-tight.

10 13. The device of claim 2, wherein the flange is made of a polyolefin, polyethylene terephthalate, polybutylene terephthalate, polyvinyl chloride, ionomer, polyurethane, nylon, polycarbonate, acrylic, ethylene vinyl acetate copolymer, polyvinylidene fluoride or blend thereof.

15 14. The device of claim 3, wherein the ring is of a springy material selected from the group consisting of engineering polymer, stainless steel, nickel titanium superelastic alloys, or elastomers.

15. The device of claim 1, wherein the enclosure is rigid and self-supporting.

20 16. The device of claim 1, wherein the enclosure is gas-tight and expandable from a first configuration to a second configuration by supplying pressurized gas to the interior of the enclosure.



-12-

17. The device of claim 11, wherein the constriction is elastically deformable.





18. The device of claim 11, wherein the enclosure is bulbous in shape at the open end thereof and the constriction forms a narrow passage through which surgical instruments can be inserted into a patient's abdominal cavity.







19. A medical device for forming an extracorporeal pneumoperitoneum extension comprising an enclosure which is open at one end thereof, the enclosure including at least one access opening therein for accessing an interior of the enclosure and allowing surgical operations to be performed beneath the abdominal wall or within the interior of the enclosure, the enclosure being gas-tight and expandable from a first configuration to a second configuration by supplying pressurized gas to the interior of the enclosure.

20. A medical device for forming an extracorporeal pneumoperitoneum extension comprising an enclosure and deploying means at an open end of the enclosure, the deploying means being deformable to a configuration which permits the open end to pass through a trocar puncture site in an abdominal wall and then expand the open end beneath an inner surface of the abdominal wall, the enclosure allowing surgical operations to be performed beneath the abdominal wall or within an interior of the enclosure, the deploying means comprising an elastically deformable annular flange and the device including an annular gap between the enclosure and the flange, the gap accommodating the abdominal wall surrounding the trocar puncture site when the flange is deployed beneath the inner surface of the abdominal wall.



2/3





INTERNATIONAL SEARCH REPORT

International application No.

PCT/US95/03140

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :A61B 17/04

US CL :606/213

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 128/DIG. 26; 604/167, 174, 178, 237, 256; 606/93-96, 201-203, 213, 215

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
NONE**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X ---, P Y	US, A, 5,366,478 (BRINKERHOFF ET AL.) 22 November 1994, see the entire document.	1-3, 11-12, 14, 16-20 ----- 1-5, 8-20
A	US, A, 5,192,301 (KAMILA ET AL.) 09 March 1993. See the entire document.	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be part of particular relevance

E earlier document published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z

document member of the same patent family

Date of the actual completion of the international search

04 MAY 1995

Date of mailing of the international search report

26 MAY 1995

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

MICHAEL PEFFLEY

Telephone No. (703) 308-4305